



Aus-Frac
12 Frankston Gardens Dr
Carrum Downs
Victoria, 3201
ABN: 26 610 150 564
Ph: (03) 9782 5855
latham.kane@gmail.com

PRODUCT DATA SHEET

AUSFRACBREAK 150

High pH Liquid Enzyme Breaker

DESCRIPTION

AUSFRACBREAK 150 is a double-strength breaker designed to break guar and derivitized guar-based fracturing fluids, as well as cellulose and its derivatives. AUSFRACBREAK 150 is highly effective up to a fluid pH of 10.0 and at temperatures below 160°F.

APPLICATION

Recommended dosage levels range from 1.89 - 3.78L. of AUSFRACBREAK 150 per 3785L. of base fluid. AUSFRACBREAK 150 can also be used in fluids that are up to 50% alcohol based. Testing is strongly recommended.

PROPERTIES

TEMPERATURE RANGE	Most effective in temperatures between 50 - 160°F. PEJOBREAK 150 can be used above 160°F, but its effectiveness will decrease as temperature increases.
PH RANGE	Up to a pH of 10.0.

All testing should be conducted once product has been approved for use.

STORAGE

PEJOBREAK 150 is stable for up to six months at 40 - 50°F with less than a 10% loss in activity.

PACKAGING

5 gal. pails, 55 gal. poly drums and 275 gal. and 330 gal. poly totes.

Please read and understand the Material Safety Data Sheet (MSDS) before using this product.