



Aus-Frac
12 Frankston Gardens Dr
Carrum Downs
Victoria, 3201
ABN: 26 610 150 564
Ph: (03) 9782 5855
latham.kane@gmail.com

PRODUCT DATA SHEET

AUSFRACBREAK 260

Powdered Breaker

DESCRIPTION

AUSFRACBREAK 260 is a powdered oxidizer for use as a breaker agent in guar and derivitized guar-based fracturing fluids. It is a powerful breaker that is both highly efficient and cost effective. The oxidizing agent in AUSFRACBREAK 260 is sodium bromate. Regarding use, testing is strongly recommended to determine the optimum load rates for each particular use.

Note that care should be taken when handling AUSFRACBREAK 260. As a strong oxidizer, it should be kept away from reducing agents, combustibles, organic materials, powdered metals and sodium peroxide.

PROPERTIES

COLOR	White, crystalline solid
ACTIVITY	At least 98%
BULK DENSITY (LBS./FT. ³)	115 – 134
SPECIFIC GRAVITY	3.33
SOLUBILITY IN WATER	28% at 77°F (25°C)
PH (1% IN WATER)	5.5 – 7.5

All testing should be conducted once product has been approved for use.

PACKAGING

25kg bags (water soluble) and 22.5L. pails.

Please read and understand the Material Safety Data Sheet (MSDS) before using this product.