



Aus-Frac
12 Frankston Gardens Dr
Carrum Downs
Victoria, 3201
ABN: 26 610 150 564
Ph: (03) 9782 5855
latham.kane@gmail.com

PRODUCT DATA SHEET

AUSFRACBREAK 450

Low Temperature Liquid Oxidizing Breaker

DESCRIPTION

AUSFRACBREAK 450 is a slurry in an environmentally friendly oil (0-BTEX) using an alkaline oxidizer as the active agent. AUSFRACBREAK 450 is used as a delayed breaker for fracturing fluids containing guar or derivitized guar-based fluids at lower temperatures.

USAGE

AUSFRACBREAK 450 can be used where an oxidizing agent is needed at temperatures above 180°F (82°C). Testing is strongly recommended.

PRODUCT FEATURES

- Breaker does not activate at ambient temperature.
- Delayed release at temperatures above 180°F.
- Liquid form for ease of addition.
- Environmentally friendly slurry containing 0-BTEX chemicals.

PROPERTIES

COLOR	White liquid slurry
ACTIVE CONCENTRATION (LBS./GAL.)	1.0
DENSITY (LBS./GAL.)	8.34
VISCOSITY	800 – 1500 cps (Brookfield RVDV)

All testing should be conducted once product has been approved for use.

PACKAGING

1000lt poly totes.

Please read and understand the Material Safety Data Sheet (MSDS) before using this product.