



Aus-Frac
12 Frankston Gardens Dr
Carrum Downs
Victoria, 3201
ABN: 26 610 150 564
Ph: (03) 9782 5855
latham.kane@gmail.com

PRODUCT DATA SHEET

AUSFRACGEL-S 403

Low Viscosity Guar Gum Slurry

DESCRIPTION

AUSFRACGEL-S 403 is a clean, natural and environmentally friendly guar gum slurry in non-regulated, 0-BTEX mineral oil for fracturing fluid applications. AUSFRACGEL-S 403 has excellent hydration properties that allow for both batch mixing and on-the-fly addition. The high quality and high purity of this product means that both lower polymer loadings can be achieved and fewer impurities are deposited downhole, in each case, resulting in cleaner, higher permeability wells.

PRODUCT FEATURES

- Builds low viscosity quickly.
- Provides greater flexibility with chemical activators.
- Cleaner polymer for less downhole residue, with greater permeability and more efficient production.
- Generates sufficient viscosities so less polymer can be used on the job and cleanup is improved.
- Ultra-high regained permeability achieved when used with PEPC's line of stimulation chemicals.
- Not regulated by the U.S. DOT.
- Environmentally friendly slurry that contains 0-BTEX chemicals.

PROPERTIES

APPEARANCE	Light beige color
PH OF 1.0% SOLUTION	6.5 – 8.0
SLURRY VISCOSITY	800 – 2500cps (Brookfield RVDV)
SLURRY CONCENTRATION (LBS./GAL.)	4.0
DENSITY (LBS./GAL.)	8.90

FANN 35 viscosity, 40 ppt gel, 2% KCl water, 2.5 minute hydration at 1500 RPM, R1B1, 300 RPM:

3 minutes	29 - 31 cps
5 minutes	30 - 32 cps
30 minutes	32 - 34 cps
60 minutes	34 - 36 cps

All testing should be conducted once product has been approved for use.

PACKAGING

200lt & 1000lt poly totes and bulk storage.

Please read and understand the Material Safety Data Sheet (MSDS) before using this product.

Page 1 of 1

Disclaimer: This information is furnished without warranty, expressed or implied, as to accuracy and/or completeness. This information is obtained from various sources including manufacturers and other third party sources, and may not be valid under certain conditions or if this material is used in combination with other materials or in any process. Any final determination of suitability of this material is the sole responsibility of the user.