



Aus-Frac  
12 Frankston Gardens Dr  
Carrum Downs  
Victoria, 3201  
ABN: 26 610 150 564  
Ph: (03) 9782 5855  
latham.kane@gmail.com

## PRODUCT DATA SHEET

# AUSFRACLINK-Z 150

Gel Crosslinker Initializer

### DESCRIPTION

AUSFRACLINK-Z 150 is a highly efficient, alcohol-based gel crosslinker for fracturing fluids based on guar and derivitized guar (particularly, CMHPG). It works in a pH range of 7.0 – 12.0 and at temperatures up to 400°F (204°C), thus making it useful for a broad range of applications.

### USAGE

AUSFRACLINK-Z 150 can be used for a wide variety of fluid systems and a broad range of temperatures. PECOLINK-Z 150 is very useful for providing initial viscosity for zirconium-based crosslinker systems at the surface at room temperature.

### APPLICATION

AUSFRACLINK-Z 150 is typically added on the fly, at recommended dosage levels ranging from 0.5 – 1.0 gal. (1.89 - 3.875lt) per 1000 gal. (3875lt) of base fluid, and at pH levels ranging from 7.0 – 12.0. pH levels ranging from 7.0 – 12.0 can be achieved by using AUSFRACBUFF 100. AUSFRACLINK-Z 150 has no known incompatibilities with any additives normally used in fracturing fluids. Testing is strongly recommended before use of this product to obtain optimum results.

### PROPERTIES

FLASH POINT	> 61°F (16°C)
COLOR	Pale yellow liquid
PH RANGE	Weakly alkaline
ODOR	Alcoholic
DENSITY (LBS./GAL.)	6.78
SPECIFIC GRAVITY	0.813
FREEZE POINT	<-20°F(-29°C)
WATER SOLUBILITY	Soluble

All testing should be conducted once product has been approved for use.

### PACKAGING

1000lt poly totes.

*Please read and understand the Material Safety Data Sheet (MSDS) before using this product.*