



Aus-Frac
12 Frankston Gardens Dr
Carrum Downs
Victoria, 3201
ABN: 26 610 150 564
Ph: (03) 9782 5855
latham.kane@gmail.com

PRODUCT DATA SHEET

AUSFRACMUL 60-M

Formation Cleaner

DESCRIPTION

AUSFRACMUL 60-M is a mixture of surfactants and a mutual solvent in a solvent base that cleans and water wets the formation for a more efficient unloading and breakdown of wells. AUSFRACMUL 60-M lowers the surface tension of water and breaks agglomerations of clays in the formation, removing blockages and lowering the breakdown pressure of the well, as well as greatly increasing production, particularly in wells producing wet gas and oil.

APPLICATION & USAGE

AUSFRACMUL 60-M can be used as a breakdown fluid, with a recommended dosage level of 15 gal. of AUSFRACMUL 60-M per 1000 gal. of breakdown fluid, applied prior to treating the well. AUSFRACMUL 60-M can also be added to the fracturing fluid, with a recommended dosage level of 1 - 2 gal. of AUSFRACMUL 60-M per 1000 gal. of base fluid. Testing is strongly recommended to determine the optimum load rates for each particular use.

PROPERTIES

COLOR	Clear liquid
PH (1% SOLUTION)	6.0 – 8.0
SPECIFIC GRAVITY	0.93 – 0.99
SURFACE TENSION (2 GPT IN WATER) (dyn/cm)	29 – 30
POUR POINT	< -25°F

All testing should be conducted once product has been approved for use.

PACKAGING

200lt or 1000lt poly totes and bulk storage.

Please read and understand the Material Safety Data Sheet (MSDS) before using this product.